Polar®

Frost Air

ELEGANT ETCHED GLASS EFFECT

Polar® Frost Air is a premium translucent matte polymeric film with a subtle embossed finish that simulates the elegant look of etched glass at a more affordable price.

It offers easy, bubble-free application with its air egress technology, requiring no water or messy application processes.

Ideal for high-end office spaces, interior décor, retail displays, and more, Polar® Frost Air delivers a professional, frosted glass effect that enhances any environment while maintaining a simple, clean installation process.

- CAN BE USED PRINTED OR UNPRINTED
- EASY, BUBBLE FREE APPLICATION
- DRY INSTALLATION - NO WATER NEEDED

Product Code: PPFA

90 micron Translucent Embossed Polymeric — Matte

(Eco) Solvent
Latex
UV

Clear
Permanent
with Bubble Free Technology

Widths up to 1520mm

5 YEARS DURABILITY — **INTERIOR & EXTERIOR**

APPLICATIONS

Indoor/Exterior Graphics

Office Environments

Retail Branding

Trade Shows

DRYTAC®
ADHESIVE SCIENCE

Polar®

Frost Air

TECHNICAL SPECIFICATION

Polar® Frost Air is a 3.6mil (90µ) high quality, translucent matte polymeric PVC film with an embossed pearl finish. It is coated with a clear permanent adhesive that is protected by a two-sided PE coated release liner with bubble-free technology.

Polar® Frost Air is compatible with Eco (Solvent), Latex, and UV print technologies, making it the ideal solution for custom window graphics for interior decor, office environments, retail branding solutions, trade shows, and more.

- IDEAL FOR INTERIOR & EXTERIOR BRANDING
- DIFFUSES LIGHT CREATING BRIGHTER VIVID IMAGES
- IDEAL FOR PRIVACY FILMS IN OFFICE ENVIRONMENTS

PRODUCT STRUCTURE

Film	Translucent Matte Polymeric PVC
Adhesive	Clear Permanent
Release Liner	2 Sided PE Coated with Bubble-Free Technology

PRODUCT CHARACTERISTICS

Film Thickness	3.6 mil (90µ)
Outdoor Durability	5 Years (unprinted)
Application Temperature	>50˚F (10˚C)
Service Temperature Range	-49˚F to 179.6˚F (-45˚C to 82˚C)
Shelf Life	2 years
Storage Conditions	59˚F to 72˚F (15˚C to 22˚C); 50 - 55% Relative Humidity

DRYTAC®

ADHESIVE SCIENCE

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2024 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

Europe
Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada
30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA
5401 B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013