

ReTac®

Smooth 75

ReTac® Smooth 75 is 75µ (3 mil), printable white polymeric PVC film coated on one side with ReTac® ultra removable adhesive. With ReTac® adhesive technology, there is no need to worry about surface damage during graphic removal. ReTac® Smooth 75 can be removed and repositioned multiple times without a decrease in bond strength. It has a Class 0 fire rating, making it ideal for use on most indoor surfaces and for applications in public areas that require compliance with strict fire regulations, such as airports, hotels and hospitals.

- IDEAL FOR INTERIOR PROMOTIONS
- PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS

Product Code: RTM

**75
micron**

White
Phthalate-Free
Polymeric
PVC

Matte



(Eco)Solvent
Latex
UV



ReTac® ultra removable
and re-positionable
adhesive



Widths up to 1370mm



INTERIOR AND EXTERIOR
(2 YEAR REMOVABILITY EXTERIOR)

APPLICATIONS

Curved Surfaces
Exhibition Graphics
Interior Décor
Removable Decals

Certified for
HP Latex Inks

EASY APPLICATION AND REMOVAL



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

ReTac®

Smooth 75

ReTac® Smooth 75 is a 75µ (3 mil) printable matte white, phthalate-free polymeric PVC film, coated on one side with ReTac® ultra removable adhesive. The adhesive is protected by a single-sided, siliconised PE coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy application and removal of vibrant graphics to a wide range of substrates. ReTac® Smooth 75 can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- RETAC® IS A PHTHALATE-FREE FILM.
- IDEAL FOR REMOVABLE WALL DECALS, APPLIQUÉS AND WALL MURALS.
- SUITABLE FOR USE ON MOST INDOOR SURFACES, PAINTED WALLS, MELAMINE, AND GLASS.
- RETAC® SMOOTH 75 HAS SEVERAL FIRE RATINGS, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS.

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal, for more information please contact your local representative.

**For more information,
performance and warranty
guidelines please contact your
local Drytac office.**

© 2022 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.

05132022

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte White Polymeric PVC
Adhesive	ReTac® ultra removable and re-positionable adhesive technology
Release Liner	88# (143gsm) 1 side siliconized PE coated Kraft paper

PRODUCT CHARACTERISTICS

Film Thickness	3 mil (75µ) 3.7 mil (93µ)
Adhesive Layer	0.7 mil (18µ)
Outdoor Durability	5 year; 2 years removability
Application Temperature	>41°F (5°C)
Service Temperature Range	40°F to 120°F (4.4°C to 48.9°C)
Flame Ratings	Class 0 (BS 476 - Part 6 & 7) Class C-s1, d0 (EN 13501-1) PASS (CAN/ULC-S102)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using ReTac® Smooth 75, an overlaminate can be used for maximum life expectancy. Products recommended for use with ReTac® Smooth 75 are Drytac's Weathershield® overlaminates.

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401 B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com