

SpotOn®

White M50

Perfect for window graphics and for short-term indoor applications such as wall, tradeshow or retail graphics that require seasonal change out. SpotOn® White M50 is 50% more opaque than standard SpotOn® White products. This high quality, ink receptive printable vinyl has an unique dot pattern removable adhesive that is virtually undetectable, but allows graphics to be installed with minimal effort, remain in place for the duration of the application, and removed with ease. The film's adhesive allows for easy, bubble-free application of vibrant graphics to a wide range of substrates without the need for tools or wet installation.

- 50% MORE OPAQUE THAN STANDARD SPOTON WHITE PRODUCTS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

Product Code: SPOE

100
micron

Matte
Monomeric
PVC

Matte



(Eco)Solvent
Latex
UV



DOT Pattern
Removable
Adhesive



Widths up to 1370mm



INTERIOR



EXTERIOR

EASY BUBBLE FREE APPLICATION

50% OFF

www.drytac.com

APPLICATIONS

Indoor Signage
Retail Promotions
Window Graphics
Wall Graphics



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com



White M50

SpotOn® White M50 is a 4 mil (100µ) printable white matte monomeric PVC film with a dot-patterned, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconized clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy, bubble-free application of vibrant graphics to a wide range of substrates. The light block properties of SpotOn® White M50 make it up to 50% more opaque than the standard SpotOn® White product.

- IDEAL FOR SHORT-TERM INDOOR WALL AND WINDOW APPLICATIONS
- INCREASED OPAQUENESS PREVENTS SHOW THROUGH FROM THE SUBSTRATE
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

INSTALLATION

RECOMMENDATION

Please see SpotOn® installation instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	White Matte Monomeric PVC
Adhesive	Dot Pattern Removable Polyacrylate
Release Liner	135 gsm Siliconized 1 Side Bleached Clay Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	4 mil (100µ)	4.5 mil (113µ)
Adhesive Layer	0.5 mil (13µ)	
Film/Adhesive Ratio	4:0.5	
UV Protection Factor	Not Applicable	
Outdoor Durability	6 months	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Flame Retardancy	B1 (According to DIN 4102-1)	
Shelf Life	1 year	
Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity	

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com