



DISPA® is a multilayered, 100% fibre-based board with a unique non-directional core layer. It offers excellent flatness and dimensional stability. Its lightweight construction enables easy handling while remaining compatible with major processing methods.

Applications

Short term promotional campaigns • Hanging signs • Point of sale displays • Photo mounting

Print suitability

UV • Screen print

Conversion suitability

Die cutting • Guillotining

Specification		
Thickness (mm)	3.8	5.0
Weight (gsm)	840	870
Sheet width tolerance (mm)	± 5	± 5
Sheet length tolerance (mm)	± 5	± 5
Sheet thickness tolerance (mm)	± 0.4	± 0.4
Weight per unit area tolerance (%)	± 5	± 5
Tolerance in right angle (mm/m)	± 1	± 1
Smoothness (Bekk S) ISO 5627	51	51
Bending strength (N/mm²)	4.0	2.7
pH value (Neutral=7) ISO 6588	9.0	9.0

Stock schedule		
mm	3.8	5.0
1016mm x 1524mm	●	
1250mm x 1840mm	●	●
1250mm x 2450mm	●	
1524mm x 3048mm	●	

Also available in 2.4mm as mill making.

● Stocked ● Available from mill

Credentials



This information is given for general guidance only and is subject to change without notice.